

Ordering Information

Part Number	Description	Unit
HFL-8150N-060602-H1	G4 IPS, Natural White, 150LEDs (3528 SMD), 0.6m, 100~130VAC, Milky Lens	pcs
HFL-8300N-120602-H1	G4 IPS, Natural White, 300LEDs (3528 SMD), 1.2m, 100~130VAC, Milky Lens	pcs
HFL-8360N-150602-H1	G4 IPS, Natural White, 360LEDs (3528 SMD), 1.5m, 100~130VAC, Milky Lens	pcs
HFL-8150N-060602-H2	G4 IPS, Natural White, 150LEDs (3528 SMD), 0.6m, 190~277VAC, Milky Lens	pcs
HFL-8300N-120602-H2	G4 IPS, Natural White, 300LEDs (3528 SMD), 1.2m, 190~277VAC, Milky Lens	pcs
HFL-8360N-150602-H2	G4 IPS, Natural White, 360LEDs (3528 SMD), 1.5m, 190~277VAC, Milky Lens	pcs

Technical Specifications

Physical Specifications

Length	600 mm (1.96 ft)	1200 mm (3.93 ft)	1500 mm (4.92 ft)
Weight	240g	490g	610g
Housing	Aluminum		
Cover	Milky PC		
Tube Diameter	T8		
Base Type	G13		
Work Environment	Indoor use (applicable for dry environment)		

Electrical Specifications

	600 mm (1.96 ft)	1200 mm (3.93 ft)	1500 mm (4.92 ft)
LED Quantity	150LEDs	300LEDs	360LEDs
Power Consumption	10W ±2W	20W ±2W	25W ±2W
Input Voltage	100~130VAC/190~277VAC		
Power Factor	>0.92		
Lighting Source	SMD LEDs		
Operation Temperature	-20~40°C (-4~104°F)		

Optical Specifications

	600 mm (1.96 ft)	1200 mm (3.93 ft)	1500 mm (4.92 ft)
Lumens	680~720 lm	1350~1450 lm	1700~1800 lm
Color Range	White		
Color Temperature	6000~6500K		
CRI	>65		
Beam Angle	120°		